

RPCM combines remote power control, automatic transfer switch (ATS), icmp/tcp port/consumption based watchdogs with automatic power reset, short circuit protection, overload protection and power consumption metering per output, high in-rush current avoidance, integration via SNMP/REST API - all in a single device



Model	1502	
Power rating	3840 VA (240V)	
Inlets	Connection type	2 x IEC-320-C20 connectors
	Voltage and current rating	100-240V (1 phase+neutral+protective conductor (protective ground)), 16A
	Frequency	50/60 Hz ± 5%
	Transfer time between inlets	From 3.5 to 14 ms
Outlets	Grounding control	Indication of grounding presence/absence
	Connection type	10 x IEC-320-C13 connectors
	Voltage and current rating	100-240V (1 phase+neutral+protective conductor (protective ground)), 10A
	Overcurrent and Short Circuit Protection Parameters	Overload protection: configurable 0.1-10A (default setting 10A) Short circuit protection: 7-17 x iNom (triggers at a short-circuit current of 75A)
	Power consumption metering	Separate power consumption metering on each outlet
Indicator lights	Power-on delay between outlets	Programmable (default delay 1 second)
	Cords fixation	Power cables fixation kit (option)
Indicator lights	Inlet state	- On/Off/Incorrect inlet voltage/Priority - Current/Voltage - Grounding indication presence/absence
	Channels (outlets) state	On/Off/Short circuit/Outlet overcurrent/Inlet overcurrent
Remote control and remote monitoring	Inlet state	- On/Off/Incorrect inlet voltage/Priority - Frequency/Voltage/Current/Wattage - Grounding indication presence/absence
	Channels state	- On/Off/Short circuit/Outlet overcurrent/Inlet overcurrent - Managing current cutoff thresholds and power-on delay
	Power consumption metering	Separate power consumption metering on each outlet
	Supported protocols	- HTTP/HTTPS (WEB Interface/REST API) - SSH - SNMPv1, SNMPv2c, SNMPv3, SNMP Traps - SMTP
Standard compliance	Automation (Watchdog)	- Output channel (outlet) reset, if there are no responses to ICMP requests (pings) - Output channel (outlet) reset, if the TCP port is unavailable - Output channel (outlet) reset, when the current decreases - Output channel (outlet) reset, if the miners hash rate decreases
	Electromagnetic compatibility	CE (EN55032, EN55024, EN61000) EAC (GOST30804 (IEC61000), GOST51317 (IEC61000))
General parametres	Safety	CE (EN60950), EAC (GOST51321 (IEC60439))
	Communication interface	Ethernet 10/100 Mbps
	Accessories included	Fixtures for installation in a 19 inch rack, 2 x inlet cables (C20 to Euro/Schuko) 2.0m, quick install guide
	Available options	Extended fixtures for installation in a 19 inch rack, power cable organizer
	Size (width x depth x height)	440 x 365 x 44 mm, takes a standard 1U slot in a 19 inch rack
	Module weight/included accessories/total weight with packaging (kg)	5.2/1.21/8.13
	Operating temperature	0 ~ +40 °C
	Storage temperature	-20 ~ +60 °C
	Operating humidity	45 ~ 85 % (no condensation)
Cooling	Passive	
Noise level	Under 30 dBA (powering on/off and switching ports)	



All the information is purely of a reference nature and is not a public offer as defined by provisions of Article 437 of the Civil Code of the Russian Federation. The product specification, the exterior appearance and the exact supplied configuration may be changed by the developer without prior notice.